

SPECIFICATION

| | | |
|-----------------------|---|--------------------------------|
| TV SYSTEM | MK-2321E | MK-2321C |
| IMAGE SENSOR DEVICE | 1/3-inch interline transfer CCD | |
| IMAGE SENSOR AREA | 4.8mm(H)×3.6mm(V) | |
| HORIZONTAL FREQUENCY | 15.750KHz | 15.625KHz |
| VERTICAL FREQUENCY | 60Hz | 50Hz |
| TOTAL PIXELS | 542(H)×492(V) | 542(H)×582(V) |
| SCANNING SYSTEM | 525 lines,60 fields/sec | 625 lines,50 fields/sec |
| MINIMUM ILLUMINATION | 0.1 lux at F1.4 | |
| RESOLUTION | 420 TV lines | |
| AUTO IRIS | VIDEO / DD lens | |
| SIGNAL TO NOISE RATIO | Better than 48dB | |
| ELECTRONIC SHUTTER | A.E.S.: 1/60(50) to 1/100000 sec. continual | |
| VIDEO OUTPUT | 1.0 Vp-p composite video at 75 ohm load | |
| GAMMA CORRECTION | 0.45 | |
| GAIN CONTROL | Auto gain control | |
| MIRROR FUNCTION | ON/OFF Switchable | |
| FIXING MOUNT | Standard camera thread, top and bottom(1/4"x20) | |
| OPERATION TEMPERATURE | - 20 °C TO 55°C | |
| OPERATIONAL HUMIDITY | within 85% RH | |
| POWER SOURCE | 12V DC ±10% | |
| LENS MOUNT | Standard C & CS mount | |
| DIMENSIONS | 50.5mm(W) X 50.5mm(H) X 65mm(L) | |
| WEIGHT | 230g | |
| CONNECTORS | VIDEO POWER AUTO IRIS | BNC DC-JACK 4P Mini-JACK |

* The specifications and appearance of the product may changed without notice.

DIMENSION (UNIT:mm)

